

CP-DNW-HPU24G2F1-30

27 Ports Switch with 24 PoE Ports & 2 Gigabit + 1 SFP Uplink Port

- Port 1-24 support PoE, Max. 30W Output of Single PoE Port
- Support IEEE802.3/802.3u/802.3z/802.3ab/802.3x
- 2, 1000Mbps & 1 Gigabit SFP Uplink port; Transmission Distance: Default: 0-100m
- Easy and safe Installation



System Overview

As most of the CP PLUS products have been integrated with the Power of Ethernet technology which makes troubleshooting easier in case any errors occur. This can be done with the help of a PoE Switch makes increases reliability rapidly.

Functions

Easy to Use

This PoE Switch is quite easy to install and use. It requires no configuration and installation. With outstanding performance.



CP-DNW-HPU24G2F1-30

27 Ports Switch with 24 PoE Ports & 2 Gigabit + 1 SFP Uplink Port

Functions

Switching Performance

This PoE Switch offers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss.

Better Connectivity

This PoE Switch has designed for outstanding power with flexible placement for better and advanced connectivity between network devices.

LED Indicator

LED lights have been installed in this Ethernet Switch to work as indicators for you to realize simple work statement reminders and clear the troubles.

6KV Surge Protection

6KV is an internal electrical wiring standard which means that when large currents enter the device, the clamping voltage increases as well, so there will be a large amount of destructive energy getting passed through the 6kv protection. The 6kv surge protection is a feature in this PoE Switch that was designed to protect all the connected electrical devices from voltage spikes.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-DNW-HPU24G2F1-30

27 Ports Switch with 24 PoE Ports & 2 Gigabit + 1 SFP Uplink Port

Feature	Specification
Uplink Ports	2, 1000Mbps & 1 Gigabit SFP Uplink port; Transmission Distance: Default: 0-100m
PoE Ports	Port 1-24 support PoE, Max. 30W Output of Single PoE Port
Switch Capacity	10.8 Gbps (non-blocking)
Packet Forwarding Rate	8.035 Mpps
Network Standard	IEEE802.3/802.3u/802.3z/802.3ab/802.3x
Network Ports	27
Transmission Distance	0-100m/1000Mbps or Port 9-24 Max. 250m/10Mbps via Cat.5e or more under Extend
MAC Address List	2K
Packet Buffer	1.5Mb
ESD Protection	Air discharge: 8KV Contact discharge: 6KV
VLAN	Support
Forwarding Mode	Store-and-forward
SW(DIP Indicator)	Green light off: Normal mode Green light on: VLAN mode Green light flash: Extend mode
PWR (Power supply Indicator)	Light on: Powering Light off: No Power
RJ-45 ACT Indicator	Green light off: Link is disconnected Green light on: Link is connected Green light flash: Data Transmitting
Surge Protection	Common mode/RJ45 port: 4KV Differential mode/RJ45 port: 2KV Common mode/Power board: 4KV Differential mode/Power board: 2KV

Feature	Specification
Network Medium	10Base-T : Cat3,4,5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)
PoE Standard	IEEE802.3af, IEEE802.3at
PoE Power Budget	300W
PoE Power Supply	1/2(+), 3/6(-)
Operating Temperature	-20°C ~ 45°C
Storage Temperature	-45°C ~ 85°C
Humidity	10%-95%, non-condensing
Power Source	Built-in Power Supply Input: 100-240V AC, 50/60Hz
Power Consumption	<5W
Color	Black
Dimensions	320mm x 207mm x 45mm
Weight	1.8Kg (without packaging)

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com