


CP-ENC-T21PL3C-GP

2MP Full-color Guard+ Network Bullet Camera - 30Mtr.

- 1/3" 2MP PS CMOS Image Sensor (0.84667cm)
- 1920(H) × 1080(V) @30fps
- H.265/H.264/JPEG/AVI/MJPEG
- DWDR, BLC, HLC, White Balance
- 2.8mm fixed lens (3.6mm optional)
- Illumination Range of 30 Mtrs, IP66, PoE
- Mobile Software: sMOB
- CMS Software: SVMS Pro



System Overview

With features of simple installation, easy operation, and high performance-cost ratio, This Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Functions

Live Viewing

Unlike some, this technology enables you to record the picture feed but view it live as well at your convenience. On top of that, the advantages of high-resolution video recording are numerous.



CP-ENC-T21PL3C-GP

2MP Full-color Guard+ Network Bullet Camera -
30Mtr.

Functions

True Day/Night (ICR)

When the scene is too dark, the image is captured by illuminating an infrared light through the camera onto the scene that greatly helps with making the scene visible for the lens. It delivers color images during the day and automatically switches to the monochrome feature as the scene darkens.

Power over Ethernet

This product uses the latest PoE technology to troubleshoot the occurrence of any issues in the system making it easier to use. With the help of this technology, your camera now only consumes energy directly from the power supply and doesn't require any mid-way switches.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-ENC-T21PL3C-GP

2MP Full-color Guard+ Network Bullet Camera -
30Mtr.

Feature	Specification
Image Sensor	1/3" 2MP PS CMOS Image Sensor (0.84667cm)
Minimum Illumination	Color: 0.04 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
Effective Pixels	1920 (H) × 1080 (V)
Shutter Speed	Auto: 1/3-1/100000Sec
Lens	2.8mm Fixed Lens (3.6mm optional)
Gain Control(AGC)	Support
Max. Aperture	F2.0
Video Compression	H.265/H.264/JPEG/AVI/MJPEG
Angle of View	2.8 mm, horizontal FOV 95°, vertical FOV 53°, diagonal FOV 114° 3.6 mm, horizontal FOV 73°, vertical FOV 40°, diagonal FOV 88°
Back Light Compensation	BLC/ DWDR
S/N Ratio	60dB
Resolution	2MP (1920 x 1080)
Frame Rate	Main Stream 1: 1920x1080@30fps Main Stream 2: 1280x720@30fps, Sub Stream 1:720x480@30fps, Sub Stream 2:640x360@30fps, Sub Stream 3:352x288@30fps
Motion detection	Support
Privacy Mask	3 Rectangular Zone
Reset Button	Optional
Audio Compression	G711A/U
TV System	PAL/NTSC
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, Anti Flicker, HLC, Distortion

Feature	Specification
Protocol	TCP/IP,IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ,PPPoE, NTP, SMTP, UDP,Qos,802.1x,PPPoE,ONVIF 19.12(Profile S/T)
Recording Mode	NVR/CMS/Web
Ethernet	RJ-45 (10/100Base-T)
Illumination Distance	Illumination Distance 30 Mtr.
Illumination Control	Auto
Smart Phone	iPhone, iPad, Android Phone
Browser	IE8-11, Google Chrome, Firefox , Mac Safari
POE	Internal, Support IEEE 802.3af
Illumination Number	2(Warm Light)
Focus Control	Fixed
IVS	Intrusion Detetion,motion detection based on human detection
Built in Mic	Support
Weatherproof Standard	IP66
Operating Temperature	'-20°C ~ +50°C RH95% Max
Storage Temperature	'-20°C ~ +50°C RH95% Max
Power Source	DC12V±10%, 700mA
Casing	Plastic
Dimension	174(W) x 67.9(H) x 69.8(D)mm
Weight	295gm